

Module 1

Artemis

Introduction

Artemis is a DNA viewer and annotation tool, free to download and use, written by Kim Rutherford from the Sanger Institute (Rutherford *et al.*, 2000). The program allows the user to view a range of files, from simple sequence files (e.g. fasta format) to EMBL/Genbank entries, as well as the results of sequence analyses, in a highly interactive and intuitive graphical format. Artemis is routinely used by the Pathogen Genomics group for annotation and analysis of both prokaryotic and eukaryotic genomes, and can also be used to visualise mapped data from next generation sequencing. Several types/sets of information can be viewed simultaneously within different contexts. For example, Artemis gives you the two views of the same genome region, so you can zoom in to inspect detailed DNA sequence motifs, and also zoom out to view local gene architecture (e.g. operons), or even an entire chromosome or genome, all within one screen. It is also possible to perform analyses within Artemis and save the output for future reference.

Aims

The aim of this Module is for you to become familiar with the basic functions of Artemis using a series of worked examples. These examples are designed to take you through the most immediately useful functions. However, there will be time, and encouragement, for you to explore other menus; features of Artemis that are not described in the exercises in this manual, but which may be of particular interest to some users. Like all the Modules in this workshop, please remember:

IF YOU DON' T UNDERSTAND, PLEASE ASK!


Artemis Exercise 1

1. Starting up the Artemis software

Double click the Artemis icon on the desktop.

A small start-up window will appear (see below). The directory **Module_1_Artemis** contains all files you will need for this module.

Now follow the sequence of numbers to load up the *Salmonella* Typhi chromosome sequence. Ask a demonstrator for help if you have any problems.




1 Click 'File'
2 Then 'Open'

In the 'Options' menu you can switch between prokaryotic and eukaryotic mode.

You can also start Artemis from the terminal window by typing 'art'.

For simplicity it is a good idea to open a new start up window for each Artemis session and close down any sessions once you have finished an exercise.



3 Single click to select file S_typhi.dna


4 Single click to open file in Artemis then wait

Change to 'All Files' if you want to display all the files in the directory.

Use this feature to choose the type of file to be displayed in this panel. DNA sequence files will have the suffix '.dna'. Annotation files end with '.tab'. You can also open '.embl' files.

2. Loading an annotation file (entry) into Artemis

Hopefully you will now have an Artemis window like this! If not, ask a demonstrator for assistance.



Now follow the numbers to load the annotation file for the *Salmonella* Typhi chromosome.

1

Click 'File' then 'Read an Entry'

Entry = file

What's an "Entry"? It's a file of DNA and/or features which can be overlaid onto the sequence information displayed in the main Artemis view panel.

2

Single click to select file S_typhi.tab

3

Single click to open file in Artemis then wait (click 'no' if an error window pops up)

3. The basics of Artemis

Now you have an Artemis window open let's look at what's in there.

The screenshot displays the Artemis genome browser interface. At the top, there are menu options: File, Entries, Select, View, Goto, Edit, Create, Run, Graph, Display. Below the menu, the 'Entry' field shows 'S_typhi.dna' and 'S_typhi.tab'. The 'Selected feature' section displays details for 'STY0004' (bases 1287, amino acids 428, gene 'thrC', product 'threonine synthase').

The main panel shows a DNA sequence with various features represented by colored boxes. The sequence is shown in both forward (top) and reverse (bottom) strands. Stop codons are marked with black vertical bars. Genes and other annotated features are displayed as colored boxes. The features are: STY0001, STY0003, STY0004, STY0007, misc_feature, STY0005, and STY0006.

The zoomed-in view at the bottom shows the nucleotide sequence and the corresponding amino acid sequence. The amino acid sequence is: R D Y V W L Q E I I T G E I D * K # I Y R Q Q H M N K F R N V I N L K I Y * L R R A D T L T E I T S G C K R S # Q G K L I E N K Y I A S S T * T S F G M * S I # K F I D G G Q I L # P R L R L V A R D H N R G N * L K I N I S P A A H E Q V S E C D Q F K N L L T + A R Y F N A G A G A T T A C G T C T G G T T G C A A G A G A T C A T A A C A G G G A A T T G A T T G A A A A T A A A T A T A T G C C A G A G C A C A T G A C C A A G T T T O G G A A T G T G A T C A A T T A A A A T T T T G A C T A G C G G G C A G A T T T A A C C T C T C T A A T G C A G A C C A A C G T T C T C T A G T A T T G C C C C T T A A C T A A C T T T A T T A T A T A G C G G T C G T C G T A C T T G T T C A A A G C C T T A C A C T A G T T A A T T T T A A A T A A C T G A A T C G C G C G T C T A T G A A A T T G G S # T Q N C S I M V P S I S Q F Y I Y R W C C M F L N R F T I L K F I # Q S L R A S V K V I S I V D P Q L L D Y I S F L Y I A L L V H V L K P I H D I # F N I S K P P C I S A A S L N R R T A L S * L L L P F Q N F I F I D G A A C S C T E S H S * N L F K N V # A P L T K L W

The feature list at the bottom shows the following details:

CDS	190	255	Orthologue of E. coli thrL (LPT_ECOLI); Fasta hit to LPT_ECOLI (21 aa), 98% identity in 21 aa overlap
CDS	337	2799	Orthologue of E. coli thrA (AKIH_ECOLI); Fasta hit to AKIH_ECOLI (820 aa), 94% identity in 820 aa overlap
misc_feature	343	369	PS00324 Aspartokinase signature
misc_feature	2314	2382	PS01042 Homoserine dehydrogenase signature
CDS	2801	3730	Orthologue of E. coli thrB (KHSE_ECOLI); Fasta hit to KHSE_ECOLI (310 aa), 94% identity in 308 aa overlap
misc_feature	3068	3103	PS00627 GHMP kinases putative ATP-binding domain
CDS	3734	5020	Orthologue of E. coli thrC (THRC_ECOLI); Fasta hit to THRC_ECOLI (428 aa), 93% identity in 428 aa overlap
misc_feature	4022	4066	PS00165 Serine/threonine dehydratases pyridoxal-phosphate attachment site
CDS	5114	5887	Orthologue of E. coli yaaA (YAAA_ECOLI); Fasta hit to YAAA_ECOLI (258 aa), 86% identity in 257 aa overlap
CDS	5966	7396	c Similar to Bacillus subtilis amino acid carrier protein alst ALST 5W;ALST_BACSU (045068; P40743) fasta
misc_feature	7091	7138	c PS00873 Sodium:alanine symporter family signature
CDS	7665	8319	Fasta hit to TALA_ECOLI (316 aa), 65% identity in 311 aa overlap
misc_feature	7755	7781	PS01054 Transaldolase signature 1
misc_feature	8049	8102	PS00958 Transaldolase active site
CDS	8729	9319	Orthologue of E. coli mog (MOG_ECOLI); Fasta hit to MOG_ECOLI (195 aa), 94% identity in 192 aa overlap
misc_feature	8933	8974	PS01078 Molybdenum cofactor biosynthesis proteins signature 1

- Drop-down menus:** There's lots in there so don't worry about all the details right now.
- Entry (top line):** shows which entries are currently loaded with the default entry highlighted in yellow (this is the entry into which newly created features are created). Selected feature: the details of a selected feature are shown here; in this case gene STY0004 (yellow box surrounded by thick black line).
- This is the main **sequence view panel**. The central 2 grey lines represent the forward (top) and reverse (bottom) DNA strands. Above and below those are the 3 forward and 3 reverse reading frames. Stop codons are marked on the reading frames as black vertical bars. Genes and other annotated features (eg. Pfam and Prosite matches) are displayed as coloured boxes. We often refer to predicted genes as coding sequences or CDSs.
- This panel has a similar layout to the main panel but is zoomed in to show nucleotides and amino acids. Double click on a CDS in the main view to see the zoomed view of the start of that CDS. Note that both this and the main panel can be scrolled left and right (7, below) zoomed in and out (6, below).
- Feature panel:** This panel contains details of the various features, listed in the order that they occur on the DNA. Any selected features are highlighted. The list can be scrolled (8, below).
- Sliders** for zooming view panels.
- Sliders** for scrolling along the DNA.
- Slider** for scrolling feature list.

4. Getting around in Artemis

There are three main ways of getting to a particular DNA region in Artemis:

- the Goto drop-down menu
- the Navigator and
- the Feature Selector (which we will use in Part IV)

The best method depends on what you're trying to do. Knowing which one to use comes with practice.

4.1 The 'Goto' menu

The functions on this menu (below the Navigator option) are shortcuts for getting to locations within a selected feature or for jumping to the start or end of the DNA sequence. This is really intuitive so give it a try!

Click 'Goto'

Artemis Entry Edit: S_typhi.dna

File Entries Select View **Goto** Edit Create Run Graph Display

Entry: S_typhi.dna S_

Selected features: bases 128

Start of Selection Ctrl-G

End of Selection Ctrl-Left

Feature Start Ctrl-Right

Feature End Shift-Comma

Start of Sequence Shift-Period

End of Sequence Ctrl-Up

Feature Base Position... Ctrl-Down

Feature Amino Acid ...

misc_feature [800] [1600] [2400] [3200] [4000] [4800] [5600] [6400] [7200]

misc_feature

STY0005 STY0006

R D Y V W L Q E I I T G E I D * K # I Y R Q Q H M N K F R N V I N L K I Y * L R R A
 E I T S G C K R S # Q G K L I E N K Y I A S S T * T S F G M * S I # K F I D L G G C
 R L R L V A R D H W R G N * L K I N I S P A A H E Q V S E C D Q F K N L L T + A G
 AGAGATTACGCTCGTTCAGAGATCATACAGGGGAATGATTGAAATAAATATATGCGCAGCAGCATGAACAAGTTTCGGAATGTGATCAATTTAAATTTATTGACTTAGCGCGGCG
 [20] [40] [60] [80] [100] [120]
 TCTCTAATGACAGCAAGCTTCTCTAGTATTGTCCCTTTAACTACTTTATTATATAGCGGTGCTGCTACTGTCTCAAAGCCCTACACTAGTTAAATTTTAAATAACTGAATCGCCCGT
 . S # T Q N C S I M V P S I S Q F Y I Y R W C C M F L N R F T I L K F I # Q S L R A
 S I V D P Q L L D Y C P F N I S F L Y I A L L V H V L K P I H D I # F N I S K P P C
 L N R R T A L S * L L P F Q N F I F I D G A A C S C T E S H S * N L F K N V # A P

CDS	190	255	Orthologue of E. coli thrL (LPT_ECOLI); Fasta hit to LPT_ECOLI (21 aa), 86% identity in
CDS	337	2799	Orthologue of E. coli thrA (AKIH_ECOLI); Fasta hit to AKIH_ECOLI (820 aa), 94% identity in
misc_feature	343	369	P500324 Aspartokinase signature
misc_feature	2314	2362	P501042 Homoserine dehydrogenase signature
CDS	2801	3730	Orthologue of E. coli thrB (KHSE_ECOLI); Fasta hit to KHSE_ECOLI (310 aa), 94% identity in
misc_feature	3068	3103	P500627 GHMP kinases putative ATP-binding domain
CDS	3734	5020	Orthologue of E. coli thrC (THRC_ECOLI); Fasta hit to THRC_ECOLI (428 aa), 93% identity in
misc_feature	4022	4066	P500165 Serine/threonine dehydratases pyridoxal-phosphate attachment site
CDS	5114	5687	Orthologue of E. coli ysaK (YAAA_ECOLI); Fasta hit to YAAA_ECOLI (258 aa), 96% identity in
CDS	5966	7396	c Similar to Bacillus subtilis amino acid carrier protein a1st ALST SW:ALST_BACSU (Q45968);
misc_feature	7091	7138	P500873 Sodium:alanine symporter family signature
CDS	7665	8618	Fasta hit to TALA_ECOLI (316 aa), 65% identity in 311 aa overlap
misc_feature	7755	7781	P501054 Transaldolase signature 1
misc_feature	8049	8102	P500958 Transaldolase active site
CDS	8729	9319	Orthologue of E. coli mog (MOG_ECOLI); Fasta hit to MOG_ECOLI (195 aa), 94% identity in
misc_feature	8933	8974	P501078 Molybdenum cofactor biosynthesis proteins signature 1
CDS	8936	8943	Orthologue of E. coli ysaM (YSA_M_ECOLI); Fasta hit to YSA_M_ECOLI (280 aa), 98% identity in

It may seem that 'Goto' 'Start of Selection' and 'Goto' 'Feature Start' do the same thing. Well they do if you have a feature selected but 'Goto' 'Start of Selection' will also work for a region which you have selected by click-dragging in the main window.

So yes, give it a try!

Suggested tasks:

1. Zoom out, select / highlight a large region of sequence by clicking the left hand button and dragging the cursor then go to the start and end of this selected region.
2. Select a CDS then go to the start and end.
3. Go to the start and end of the genome sequence.
4. Select a CDS. Within it, go to a base (nucleotide) and/or amino acid of your choice.
5. Highlight a region then, from the right click menu, select 'Zoom to Selection'.

4.2 Navigator

The Navigator panel is fairly intuitive so open it up and give it a try.

Click 'Goto'
then Navigator

The screenshot shows the Artemis software interface. The top menu bar includes 'Goto', 'Edit', 'Create', 'Run', 'Graph', and 'Display'. The 'Goto' menu is open, showing options like 'Goto Base', 'Goto Feature With Gene Name', 'Goto Feature With This Qualifier Value', 'Goto Feature With This Key', 'Find Base Pattern', and 'Find Amino Acid String'. Below the menu, a list of genomic features is displayed, including CDS, misc_feature, and other annotations with their coordinates and orientations.

Check that the
appropriate search
button is on

Suggestions about where to go:

1. Think of a number between 1 and 4809037 and go to that base (notice how the cursors on the horizontal sliders move with you).
2. Your favourite gene name (it may not be there so you could try '*fts*').
3. Use '**Goto Feature With This Qualifier value**' to search the contents of all qualifiers for a particular term. For example using the word 'pseudogene' will take you to the next feature with the word 'pseudogene' in any of its qualifiers. Note how repeated clicking of the 'Goto' button takes you to the following pseudogene in the order that they occur on the chromosome.
4. Look at **Appendix VIII** which is a functional classification scheme used for the annotation of *S. Typhi*. Each CDS has a class qualifier best describing its function. Use the '**Goto Feature With This Qualifier value**' search to look for CDSs belonging to a class of interest by searching with the appropriate class values.
5. tRNA genes. Type 'tRNA' in the '**Goto Feature With This Key**'.
6. Regulator-binding DNA consensus sequence (real or made up!). Note that degenerate base values can be used (**Appendix Xa**).
7. Amino acid consensus sequences (real or made up!). You can use 'X's. Note that it searches all six reading frames regardless of whether the amino acids are encoded or not.

What are Keys and Qualifiers? See **Appendix IV**

Clearly there are many more features of Artemis which we will not have time to explain in detail. Before getting on with this next section it might be worth browsing the menus. Hopefully you will find most of them easy to understand.

Artemis Exercise 2

This part of the exercise uses the files and data you already have loaded into Artemis from Part I. By a method of your choice go to the region from bases 2188349 to 2199512 on the DNA sequence. This region is bordered by the *fbaB* gene which codes for fructose-bisphosphate aldolase. You can use the Navigator function discussed previously to get there. The region you arrive at should look similar to that shown below (maybe you have to use the zoom sliders).

The screenshot displays the Artemis genome browser interface. The main window shows a DNA sequence with various features represented by colored bars and labels. The features are organized into a list at the bottom of the window. Two callout boxes on the right side of the image point to specific features: 'CDS features' points to a green bar labeled 'STY2365', and 'Misc features' points to a yellow bar labeled 'misc_feature'.

Feature Type	Start	End	Description
CDS	190	255	Orthologue of E. coli thrL (LPT_ECOLI); Fasta hit to LPT_ECOLI (21 aa), 86% identity in 21 aa overlap
CDS	337	2799	Orthologue of E. coli thrA (AKIH_ECOLI); Fasta hit to AKIH_ECOLI (820 aa), 94% identity in 820 aa overlap
misc feature	343	369	PS00324 Aspartokinase signature
misc feature	2314	2382	PS01042 Homoserine dehydrogenase signature
CDS	2801	3730	Orthologue of E. coli thrB (KHSE_ECOLI); Fasta hit to KHSE_ECOLI (310 aa), 94% identity in 308 aa overlap
misc feature	3068	3103	PS00627 GMP kinases putative ATP-binding domain
CDS	3734	5020	Orthologue of E. coli thrC (THRC_ECOLI); Fasta hit to THRC_ECOLI (428 aa), 93% identity in 428 aa overlap
misc feature	4022	4066	PS00165 Serine/threonine dehydratases pyridoxal-phosphate attachment site
CDS	5114	5887	Orthologue of E. coli yaaA (YAAA_ECOLI); Fasta hit to YAAA_ECOLI (258 aa), 86% identity in 257 aa overlap
CDS	5966	7396	Similar to Bacillus subtilis amino acid carrier protein alaT ALST SW:ALST_BACSU (Q45068; P40743) fasta hit
misc feature	7091	7138	PS00873 Sodium:alanine symporter family signature
CDS	7665	8618	Fasta hit to TALA_ECOLI (316 aa), 65% identity in 311 aa overlap
misc feature	7755	7781	PS01054 Transaldolase signature 1
misc feature	8049	8102	PS00958 Transaldolase active site
CDS	8729	9319	Orthologue of E. coli mog (MOG_ECOLI); Fasta hit to MOG_ECOLI (195 aa), 94% identity in 192 aa overlap
misc feature	8933	8974	PS01078 Molybdenum cofactor biosynthesis proteins signature 1

Once you have found this region have a look at some of the information available:

Information to view:

Annotation

If you click on a particular feature you can view the annotation associated with it: select a CDS feature (or any other feature) and click on the 'Edit' menu and select 'Selected Feature in Editor'. A window will appear containing all the annotation that is associated with that CDS. The format for this information is constrained by that which can be submitted to the EMBL database.

Viewing amino acid or protein sequence

Click on the 'View' menu and you will see various options for viewing the bases or amino acids of the feature you have selected, in two formats i.e. EMBL (view -> selection) or fasta (view -> bases or view -> amino acids). This can be very useful when using other programs that are not integrated into Artemis e.g. those available on the Web that require you to cut and paste sequence into them.

Plots/Graphs

Feature plots can be displayed by selecting a CDS feature then clicking 'View' and 'Feature Plots'. The window which appears shows plots predicting hydrophobicity, hydrophilicity and coiled-coil regions for the protein product of the selected CDS.

In addition to looking at the fine detail of the annotated features it is also possible to look at the characteristics of the DNA covering the region displayed. This can be done by adding various plots to the display, showing different characteristics of the DNA. Some of the plots can be used to look at the protein coding potential of translation frames within the DNA, and others can be used to search for horizontally acquired DNA (such as GC frame plot).

1. To make this process faster and clearer, **switch off stop codons** by clicking with the right mouse button in the main view panel. A menu will appear with an option to de-select 'Stop Codons' (see below).
2. You will also need to temporarily **remove all of the annotated features** from the Artemis display window. In fact if you leave them on, which you can, they would be too small to see when you zoomed out to display the entire genome. To remove the annotation click on the S_typhi.tab entry button on the grey entry line of the Artemis window shown above.

2 To de-select the annotation click here.



The screenshot shows the Artemis genome browser interface. A right-click context menu is open over the main view panel. The menu items are:

- Smallest Features In Front
- Set Score Cutoffs ...
- Raise Selected Features
- Lower Selected Features
- Zoom to Selection
- Select Visible Range
- Select Visible Features
- Frame Line Features ...
- Entries
- Select
- View
- Goto
- Edit
- Create
- Write
- Run
- Start Codons
- Stop Codons
- Feature Arrows
- Feature Borders
- Feature Labels
- One Line Per Entry
- Feature Stack View
- Forward Frame Lines
- Reverse Frame Lines
- All Features On Frame Lines
- Show Source Features
- Flip Display
- Colourise Bases

A yellow callout box points to the 'Stop Codons' menu item with the text: "No stop codons shown on frame lines".

A blue callout box points to the 'S_typhi.tab' entry button in the top left of the interface with the text: "Menu item for de-selecting stop codons".

- One final tip is to **adjust the scaling** for each graph displayed before zooming out. This increases the maximum window size over which a single point for each plot is calculated. To adjust the scaling click with the right mouse button over a particular graph window. A menu will appear with an option "Set the Window size" (see above), set the window size to '20000'. You should do this for each graph displayed (if you get an error message press continue).
- You are now ready to zoom out by dragging or clicking the slider indicated below. Once you have zoomed out fully to see the entire genome you will need to adjust the smoothing of the graphs using the vertical graph sliders as before, to have a similar view to that shown below.



Click with the left mouse button in a graph window. A line and a number will appear. The number is the relative position within the genome (bps).

Click and drag to highlight a region on the main DNA line. Notice that the boundaries of this region are now marked in the graph windows that you previously clicked in.


Artemis Exercise 3

Now go to position 4409511. The next region we are looking at is defined as a *Salmonella* pathogenicity island (SPI). SPI-7, or the major Vi pathogenicity island, is ~134 kb in length and contains ~30 kb of integrated bacteriophage.

The region you should be looking at is shown below and is a classical example of a *Salmonella* pathogenicity island (SPI). The definitions of what constitutes a pathogenicity island are quite diverse. However, below is a list of characteristics which are commonly seen within these regions, as described by Hacker *et al.*, 1997.


1. Often inserted alongside stable RNAs
2. Atypical G+C contents.
3. Carry virulence-related functions
4. Often carry genes encoding transposase or integrase-like proteins
5. Unstable and self-mobilisable
6. Of limited phylogenetic distribution

Have a look in and around this region and look for some of these features.



We are going to extract this region from the whole genome sequence and perform some more detailed analysis on it. We will aim to write and save new EMBL format files which will include just the annotations and DNA for this region.

Follow the numbers on the next page to complete the task.



1
Select region by clicking with the left mouse button & dragging


2
Click 'Edit'

3
Click 'Edit subsequence (and features)'

A new Artemis window will appear displaying only the region that you highlighted

Note the entry names have changed

Note the bases have been renumbered from the first base you selected.



Note that the two entries on the grey 'Entry' line are now denoted 'no name'. They represent the same information in the same order as the original Artemis window but simply have no assigned 'Entry' names. As the sub-sequence is now viewed in a new Artemis session, this prevents the original files (S_typhi.dna and S_typhi.tab) from being over-written.

We will save the new files with relevant names to avoid confusion. So click on the 'File' menu then 'Save An Entry As' and then 'New File'. Another menu will ask you to choose one of the entries listed. At this point they will both be called 'no name'. Left click on the top entry in the list. A window will appear asking you to give this file a name. Save this file as spi7.dna

Do the same again for the second unnamed entry and save it as spi7.tab

The screenshot shows the Artemis Entry Edit interface. The 'File' menu is open, and 'Save An Entry As' is selected, which has opened a sub-menu with 'New File' chosen. Below the menu, a sequence alignment is visible with several features highlighted in different colors: yellow (CDS), green (misc_feature), blue (tRNA), and pink (misc_feature). The sequence is shown in a standard font with a color-coded bar above it indicating the features.

We are going to look at this region in more detail and to attempt to define the limits of the bacteriophage that lies within this region. Luckily for us all the phage-related genes within this region have been given a colour code number 12 (pink; for a list of the other numerical values that Artemis will display as colours for features see **Appendix IX**). We are going to use this information to select all the relevant phage genes using the Feature selector as shown below and then define the limits of the bacteriophage.

First we need to create a new entry (click 'Create' then 'New Entry'). Another entry will appear on the entry line called, you guessed it, 'no name'. We will eventually copy all our phage-related genes into here.

- 1 Click 'Select' then 'Feature Selector'
- Make sure the buttons are selected
- 2 Set Key to 'CDS' and Qualifier to 'colour'
- 3 Type search term
- 4 Click to select features containing search term
- 5 Click to view selected features in a list
- 6 feature list

The screenshot shows the Artemis software interface. The 'Artemis Feature Selector' dialog box is open, with the following settings: 'Key' is 'CDS', 'Qualifier' is 'colour', and 'Containing this text' is '12'. The 'Allow Partial Match' checkbox is checked. The 'Feature Selector' window shows a list of features with the following columns: Feature Name, Count, and Description. The features are:

Feature Name	Count	Description
CDS	<1	
tRNA	975	
misc_feature	975	
CDS	1116	
CDS	2147	
misc_feature	2777	
CDS	3504	
CDS	5472	
CDS	5905	
CDS	6571	
CDS	7373	
misc_feature	8718	
CDS	9302	
CDS	10175	
CDS	12854	
CDS	13384	
CDS	13316	

The 'All features with key "CDS" with qualifier "colour" containing text "12"' window shows a list of features with the following columns: Feature Name, Coordinates, and Description. The features are:


Feature Name	Coordinates	Description
CDS	65714 66091	no significant database hits
CDS	66179 66396	Similar to Escherichia coli prophage P2 Ogr protein SW:06R6
CDS	66494 67564	Similar to Bacteriophage P2 late gene control protein D SW:VFP
CDS	67561 68046	Similar to Bacteriophage P2 complete genome U essential tail f
CDS	68948 70826	Similar to Bacteriophage 186 protein G TR:Q37848 (EMBL:U32222
CDS	70819 70938	Similar to Bacteriophage 186 Orf52 H TR:O80316 (EMBL:U32222)
CDS	70953 71255	Similar to Bacteriophage P2 complete genome E essential tail
CDS	71310 71625	Similar to Bacteriophage P2 major tail tube protein FI SW:VFP
CDS	71835 73007	Similar to Bacteriophage P2 major tail sheath protein FI SW:VFP
CDS	73542 74264	Similar to Salmonella typhimurium invasion-associated secreta
CDS	74482 74969	Similar to Bacteriophage P2 probable tail fiber assembly prot
CDS	74579 76495	Similar to Bacteriophage P2 probable tail fiber protein SW:VFP
CDS	76492 77097	Similar to Bacteriophage P2 tail protein I SW:VPI_BFP2 (P2670)
CDS	77090 77998	Similar to Bacteriophage P2 baseplate assembly protein J SW:VFP
CDS	77895 78344	Similar to Bacteriophage P2 baseplate assembly protein W SW:VFP
CDS	78341 78919	Similar to Bacteriophage P2 baseplate assembly protein V SW:VFP
CDS	78986 79434	Similar to Bacteriophage P2 tail completion protein S SW:VPS f
CDS	79427 79858	Similar to Bacteriophage P2 tail completion protein R SW:VPR f
CDS	79854 80379	Similar to Bacteriophage P2 protein LysB protein involved in
CDS	80379 80750	no significant database hits. Contains possible membrane span
CDS	80761 81231	Similar to Serratia marcescens putative phage lysoczyme NucD TR

The genes listed in (6) are only those fitting your selection criteria. They can be copied or cut / moved in to a new entry so we can view them in isolation from the rest of the information within spi7.tab.

Firstly in window (6) select all of the CDSs shown by clicking on the 'Select' menu and then selecting 'All'. All the features listed in window (6) should now be highlighted. To copy them to another entry (file) click 'Edit' then 'Copy Selected Features To' then 'no name'. Close the two smaller feature selector windows and return to the SPI-7 Artemis window. You could rename the 'no name' entry as phage.tab, as you did before (if you can't remember how to do it have a look at page 14). Temporarily remove the features contained in 'spi7.tab' file by left clicking on the entry button on the grey entry line. Only the phage genes should remain.

Additional methods for selecting/extracting features using the Feature Selector

It is worth noting that the Feature Selector can be used in many other ways to select and extract subsets of features from the genome, using eg text or amino acid searches.



Space for a search term or amino acid motif

Defining the extent of the prophage

Even from this preliminary analysis it is clear that the prophage occupies a fairly discrete region within SPI-7 (see below). It is often useful to create a new DNA feature to define the limits of this type of genome landmark. To do this use the left mouse button to click and drag over the region that you think defines the prophage.

While the region is highlighted, click on the 'Create' menu and select 'Create feature from base range'. A feature edit window will appear. The default 'Key' value given by Artemis when creating a new feature is 'CDS'. With this 'Key' the newly created feature would automatically be put on the translation line. However, if we change this to 'misc_feature' (an option in the 'Key' drop down menu in the top left hand corner of the Edit window), Artemis will place this feature on the DNA line. This is perhaps more appropriate and is easier to visualise. You can also add a qualifier, such as '/label': select 'label' from the 'Add Qualifier' list and click 'Add Qualifier', '/label=' will appear in the text window; add text of your choice, then click 'OK'. That text will be used as a feature label to be displayed in the main sequence view panel.


To see how well you have done, tick the little box to turn on spi7.tab.

Your final task is to write out the spi7 files in EMBL submission format, and create a merged annotation and sequence file in EMBL submission format. In Artemis you are going to copy the annotation features from the '.tab' file into the '.dna' file, and then save this entry in EMBL format. Don't worry about error messages popping up. This is because not all entries are accepted by the EMBL database.

1 Click 'Select' then 'All'

2 Click 'Edit', then 'Copy Selected Features To'

3 Select 'spi7.dna'




4 Click 'File' then 'Save An Entry As'

5 'EMBL Submission Format'

6 Select 'spi7.dna'

7 Save file as spi7.embl



Now open the EMBL format file that you have just created in Artemis.

tRNA	1	64	c	possible truncated tRNA Phe.
misc_feature	1	133562	c	The major Vi antigen pathogenicity island (SPI 7)
CDS	142	1176		Weakly similar to the C-terminus of several polysaccharide biosynthesis proteins e.g. Str
CDS	1173	2537		Similar to Bacteriophage P1 Ban helicase TR:080281 (EMBL:AJ011592) (453 aa) fasta scores:
misc_feature	1803	1826		PS00017 ATP/GTP-binding site motif A (P-loop)
CDS	2530	4329		no significant database hits
CDS	4498	4803		Doubtful CDS
CDS	4931	5512		no significant database hits.
CDS	5597	6154		Weakly similar to Yersinia pestis orf 77 TR:Q9Z381 (EMBL:AL031866) (193 aa) fasta scores:
CDS	6399	7742		no significant database hits
misc_feature	7744	8180		Low G+C region containing repeat region with 10xTGGT(A/-)(T/C)AAAA(A/G)T.
CDS	8328	9107		no significant database hits. Contains a hydrophilic region in the N-terminus between resi
CDS	9218	11212		Previously sequenced Salmonella typhi topoisomerase B TopB TR:Q9RHF5 (EMBL:AF000001) (664
CDS	11880	12329		no significant database hits
CDS	12410	12628		doubtful CDS
CDS	12641	13177		Previously sequenced Salmonella typhi single strand binding protein ssB TR:Q9RHE4 (EMBL:AF

You will see that the colours of the features have now changed. This is because not all the qualifiers in the previous entry are accepted by the EMBL database, so some have not been saved in this format. This includes the '/colour' qualifier, so Artemis displays the features with default colours.

When you download sequence files from EMBL and visualize them in Artemis you will notice that they are displayed using default colours. You can customize your own annotation files with the '/colour' qualifier and chosen number (**Appendix IX**), to differentiate features. To do this you can use the Feature Selector to select certain features and annotate them all using the 'Edit', 'Change Qualifiers of Selected' function.

Artemis Exercise 4

This exercise will introduce you to database searches and will give you a first insight in the annotation of genes.


The gene you will work on is *hpcC* (STY1136). Go to this gene by using one of the different methods you have learned so far.

As you can see the gene is full with stop codons indicating that we are looking at a pseudogene. To correct the annotation we are going to use database search. Follow now the numbers in the figure below to start a database search. The search may take a couple of minutes to run; a banner will pop up to tell you when its complete (3).

The screenshot shows the Artemis software interface for editing the *S. typhi* dna entry. The main window displays a gene map with features like *hpcC* and *hpcB*. A search menu is open, showing options for various database searches. A 'fasta pro' dialog box is open, indicating the search is complete. The search results table is visible at the bottom of the screen.


Feature	Start	End	Description
CDS	1099596	1101061	Pseudogene. Similar to Escherichia coli 5-carboxymethyl-2-hydroxyumconate semialdehyde d
misc_feature	1100321	1100344	PS00687 Aldehyde dehydrogenases glutamic acid active site
misc_feature	1100405	1100440	PS00070 Aldehyde dehydrogenases cysteine active site
CDS	1101063	1101914	Similar to Escherichia coli 3,4-dihydroxyphenylacetate 2,3-dioxygenase hpcB SW:HPCB_ECOL
CDS	1101924	1102304	Similar to Escherichia coli 5-carboxymethyl-2-hydroxyumconate delta-isomerase hpcD SW:HF
CDS	1102448	1103251	Similar to Escherichia coli 2-oxo-hepta-3-ene-1,7-dioic acid hydratase hpcG SW:HPCG_ECOL
CDS	1103262	1104053	Similar to Escherichia coli 2,4-dihydroxyhept-2-ene-1,7-dioic acid aldolase hpcH or hpa
CDS	1104125	1105501	Similar to Escherichia coli putative 4-hydroxyphenylacetate permease hpaX TR:Q46984 (EME
CDS	1105511	1106407	Similar to Escherichia coli 4-hydroxyphenylacetate 3-monooxygenase operon regulatory pro
misc_feature	1106237	1106395	PS00041 Bacterial regulatory proteins, araC family signature
CDS	1106421	1107359	No significant database matches
CDS	1108783	1109088 c	Orthologue of E. coli yccD (YCCD_ECOLI); Fasta hit to YCCD_ECOLI (101 aa), 74% identity
CDS	1109088	1110908 c	Fasta hit to DNAI_ECOLI (375 aa), 35% identity in 353 aa overlap
misc_feature	1109814	1109873 c	PS00636 Nt-dnaJ domain signature
CDS	1110244	1110606	Similar to Salmonella typhimurium suppressor for copper-sensitivity a ScaA TR:Q33917 (EM
CDS	1110655	1112541	Similar to Salmonella typhimurium suppressor for copper-sensitivity B precursor ScaB TR:
CDS	1112550	1113101	Similar to Salmonella typhimurium suppressor for copper-sensitivity C precursor ScaC TR:

To view the search results click 'View', then 'Search Results', then 'fasta results'. The results will appear in a scrollable window. Scroll down to the first sequence comparison and you should see the results as shown in the next figure.




Can you see where the stop codon has been introduced into the sequence of our gene of interest? Search for the highlighted amino acid sequence in *hpcC*. Have a look if you can find the subsequent amino acids of the database hit in any of the three reading frames. You will see the sequence can be found in the second frame! What has happened? The last amino acid in common is a K then the amino acids start to differ till the stop codon. The amino acid K is coded by AAA. The next base is an A, too. This little homopolymeric region can cause trouble during DNA replication if the polymerase slips and introduces an additional 'A'. This shifts the proper reading frame into the second frame.

To correct the annotation we have to edit the CDS now. Left click on the right amino acid continuing the amino acid sequence on the second frame (have a look in the fasta results and look at the sequence of the gene in the database when you are not sure) and drag till the end of the gene. Then click 'Create' 'Feature from base range' and 'OK'. A new blue CDS feature will appear on the appropriate frame line.



As the original gene annotation is too long we have to shorten it. Click on the original *hpcC* CDS, 'Edit' 'Selected features in Editor'. A window will pop up and you can change the end position in 'location' (the end position is the last base of the stop codon).



Artemis Exercise 4 - Second part

In the first part of the exercise you have learned how to correct a gene annotation. But what if you think a gene is missing?

Remember that there are loads of genomes that were submitted to the databases several years ago and in general the annotation is not updated to take into account new data. Sometimes it is worth checking regions which look strange to you.

Go to position 2,248,400 by using one of the different methods you have learned so far. If you look carefully you will notice a region shown below which there is no predicted gene. This type of non-coding region in *Salmonella* is very unusual (this is also true for other bacteria). To determine if this non-coding region is truly as published, load the codon usage information for *Salmonella* into Artemis by following the figure below.

The file 'S_typhi.cod' contains codon usage information taken from a public website (see below).

1

Click Graph

2


Click 'Add usage plots' and select 'S_typhi.cod'

Non-coding



UUU 24.4(2445)	UCU 12.1(1212)	UAU 18.6(1864)	UGU 6.5(651)
UUC 15.6(1563)	UCC 18.5(1854)	UAC 13.3(1335)	UGC 5.8(585)
UUA 15.8(1582)	UCA 15.3(1534)	UAA 1.6(158)	UGA 1.4(145)
UUG 12.2(1222)	UGC 9.5(952)	UAG 0.5(47)	UGG 13.3(1326)
CUU 16.1(1614)	CCU 18.5(1855)	CAU 11.4(1143)	CGU 14.3(1426)
CUC 11.2(1128)	CCC 6.8(681)	CAC 7.2(725)	CCG 11.7(1178)
CUA 6.6(656)	CCA 9.3(938)	CAA 13.8(1381)	CGA 6.7(666)
CUG 34.1(3411)	CCG 14.1(1415)	CAG 27.2(2716)	CGG 8.2(822)
AUU 27.3(2729)	ACU 14.8(1476)	AAU 27.8(2699)	AGU 13.2(1319)
AUC 28.4(2837)	ACC 28.1(2812)	AAC 22.7(2266)	AGC 16.4(1639)
AUA 9.9(988)	ACA 14.4(1445)	AAA 35.4(3546)	AGA 6.8(599)
AUG 26.8(2597)	ACG 15.5(1552)	AAG 17.5(1752)	AGG 4.7(472)
GUU 28.3(2833)	GCU 17.7(1778)	GAU 33.9(3394)	GGU 19.5(1949)
GUC 15.4(1541)	GCC 21.6(2168)	GAC 28.8(1998)	GGC 21.8(2898)
GUA 12.8(1281)	GCA 21.8(2185)	GAA 34.8(3481)	GGA 12.6(1259)
GUG 19.4(1941)	GCG 19.3(1931)	GAG 28.8(2888)	GGG 13.6(1359)

Codon usage table taken from:
www.kazusa.or.jp/codon

When you first load the codon table into Artemis the graphs calculated for both upper and lower strands will be displayed (not shown). To add/remove one of these to/from the view click on the Graph menu and check the box alongside the option 'codon usage scores from S_typhi.cod' (the reverse plot is also represented in this list).



Based on the codon usage table Artemis calculates for each triplet in succession a score based on how well it matches the commonly used codons in that organism. The three lines shown above represent the scores for each reading frame. If the codons for a particular frame match those of the calculated codon usage table a high score is given. Practically speaking this manifests itself as a 'coding bubble' where a gap opens up in the plot indicating that this region is likely to be coding (see above). The plot suggests that this empty region actually encodes a product. So now we have to create the open reading frame (ORF), blast the amino acid sequence and add the annotation. Follow the instruction on the next page to do this.



To view the search results click 'View', then 'Search Results', then 'blastp results'. The results will appear in a scrollable window. You see that the product of the gene is "NAD-dependent dihydropyrimidine dehydrogenase subunit PreA). To add the product to the annotation follow the instruction in the next page.

1 Click on ORF

2 'Edit', 'Selected feature in editor'

3 Select 'product' from dropdown list

4 Click 'Add qualifier'

5 Add result from blast search

The annotation of the ORF is now complete. You can add as much information as you want. Have a look at the other qualifiers if some time is left. The last thing you have to do is copy the annotated feature to `S_typhi.tab`. To do that select the feature and go to 'Edit', 'Copy selected features to' and click '`S_typhi.tab`'. Don't forget to save the tab file.